

商品名

Photo	注文番号	長さ 内容量	種類	標準ノズルサイズ																												
				HD 605	HD 4/8 C	HD 7/15 C	HD 7/15 CX	HD 7/10 C Food	HD 9/17 M	HD 9/17 MX	HD 10/22 S	HD 10/22 SX	HD 13/15 S	HDS 4/7 U	HDS 4/6 C	HDS Super M Eco	HDS 7/13 C	HDS 8/14 C	HDS 8/14 CX	HDS 8/15 M	HDS 8/17 M	HDS 8/17 MX	HDS 10/19 M	HDS 13/15 S	HD 5/14 B	HD 830 BS	HD 728 B	HD 801 B 7L-4	HD 1050 B	HD 1050 B 7L-1	HDS 801 B	HDS 1000 BE
				冷水タイプ														温水タイプ							エンジンタイプ							

■高圧ホース

トリガーガン組込タイプ	1	6.389-853.0	10m	ID 6/155℃/250bar																														
	2	6.390-174.0	15m	ID 6/155℃/250bar																														
	3	6.390-185.0	15m	ID 8/155℃/315bar																														
	4	6.391-238.0	10m	ID 6/155℃/200bar	●	●	●		●			●												●				●	●					
	5	6.391-417.0	15m	両端組込タイプ				●			●																							
ロングライフ (耐高圧、長寿命タイプ)	6	6.391-351.0	10m	ID 8/115℃/400bar																														
	7	6.390-208.0	20m	ID 8/155℃/400bar										○																				
	8	6.391-977.0	25m	ID 8/155℃/400bar										○																				
	9	6.391-979.0	30m	ID 8/155℃/400bar										○																				
食品用	10	6.390-208.0	20m	ID 8/155℃/400bar																	●													
	11	6.390-445.0	15m	グレイ ID 6/155℃/315bar														○		○	○	○					○	○	○					
	12	6.390-704.0	10m	グレイ ID 8/155℃/230bar														○												○	○			
	13	6.390-705.0	20m	グレイ ID 8/155℃/160bar														○												○	○			
延長高圧ホース	14	6.391-654.0	15m	ID 6/155℃/230bar				●																										
	15	6.391-342.0	10m	ID 8/155℃/315bar	○	○	○					○																						
	16	6.390-010.0	15m	ID 8/155℃/315bar	○	○	○							○																				
	17	6.390-031.0	20m	ID 8/155℃/315bar	○	○	○							○																				
	ロングライフ (耐高圧、長寿命タイプ)	18	6.391-354.0	10m	ID 8/155℃/400bar	○	○	○						○	●	○	●	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
		19	6.390-027.0	20m	ID 8/155℃/400bar	○	○	○						○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
		20	6.391-978.0	25m	ID 8/155℃/400bar	○	○	○						○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
	食品用	21	6.390-294.0	30m	ID 8/155℃/400bar	○	○	○						○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
22		6.389-479.0	10m	ID 8/155℃	○	○	○						○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
23		6.389-581.0	20m	ID 8/155℃	○	○	○						○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
食品用高圧ホースロングライフ ¹⁾ 耐熱温度:155℃ 耐圧:40MPa	片側AVS(黄色プロテクター)	24	6.391-864.0	10m延長	○	○	○						○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○		
	片側AVS(黄色プロテクター)	25	6.391-887.0	20m延長	○	○	○						○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	

■カップリング

ねじれ防止用 オスネジM22×1.5+メスネジM22×1.5	延長高圧ホースのねじれ防止に (本体側)	26	4.401-091.0					○	○	○		○	○				○	○	○		○	○	○	○		○	○	○	○	○	○	○	○
延長用		27	4.403-002.0	両端オスネジM22×1.5 本体裏ちゅう装、外側ゴムカバー 注意:ロックタイト(接着剤)でしっかり固定	○	○	○					○	○	○				○	○	○		○	○	○	○		○	○	○	○	○	○	○
ワンタッチカップリング	オス側	28	6.463-025.0		○	○	○					○	○	○				○	○	○		○	○	○	○		○	○	○	○	○	○	○
	メス側(高圧ホース側)	29	6.463-023.0		○	○	○					○	○	○				○	○	○		○	○	○	○		○	○	○	○	○	○	○

■ホースリールマウントキット

		30	2.637-880.0	30m巻																													○	
		31	2.637-733.0	20m巻																														○
		32	2.637-998.0	20m巻																			○											

■トリガーガン

組込タイプ		33	4.775-270.0																															
		34	4.775-463.0																															
	ロングタイプ	35	4.775-554.0	450mm		●				●																								
		36	4.775-298.0	450mm																														
	37	4.775-529.0	450mm		●																													
サーボプレス (圧力水量を手元で調整可)	38	4.775-363.0																																
	39	4.775-463.0+4.775-470.0		トリガーガン式からサーボプレスユニットを組み合わせる方式に変更 4.775-470.0,4.775-471.0と組み合わせて使用					●	●		●	●								●													
延長高圧ホース直付けタイプ	サーボプレスユニット	40	4.775-466.0																															
		41	4.775-470.0																															
	42	4.775-471.0																																

●標準装備 ○オプション
 1) HD 7/15 C, CX と HD 9/17 M, MX 以外の機種の場合は、延長高圧ホースを利用することで使用ができます。